

ZLN.105F.861.CLLNP

Shell body style / Model id: ZL - Fixed hermetic receptacle

Locking system: Push-pull

Housing material: Brass

Contact Type: PCB straight female contact


Insulator: PPS

Socket / Receptacle: Fixed panel rear mounted

Suggested matching part: [TGN.105F.861.CLAD55](#)

[TGN.105F.861.CLAD55Z](#)




[TLN.105F.861.CLAD55](#)



Illustrations are simplified for illustrative purposes only

Ask for 3D models and detailed dimensions

ella_spring@vip.163.com

Electrical Configuration		
Number of contacts Mixed Contact	6+1	
Contact Dia.	6*1.3 mm +1*2.0 mm	
Panel cut-out diameter (ΦA)	20.1 mm	
Keying	1 key (arc-shape guides)	

Pulling and Inserting Times	>3000
Humidity	Max. 95% at 40 °C
Temperature	-55 °C ~+145 °C
Vibration	10~20000HZ,15g
Mechanical Shock	100g·6ms
IP Rating	IP68
R (max)	6*≤5.0mΩ + 1*≤3.0mΩ
Rated Current(A)	6*10.0 + 1*18.0
Rated Voltage(V)	6*875 + 1*875
Wire Size/AWG	6*20 + 1*14~16